

# SPECIFICATIONS



## IPA™ 75T II Industrial Power Amplifier

### SPECIFICATIONS

**Output Power:**  
75 watts

**Frequency Response:**  
Direct:  $\pm 0.5$  dB, 20 Hz to 20 kHz  
XFMR:  $\pm 0.5$  dB, 50 Hz to 20 kHz

**Distortion:**  
0.03% (1 kHz)

**S/N Ratio (20 kHz BW):**  
95 dB

**Power Bandwidth:**  
Direct: 20 Hz to 20 kHz  $< 0.5\%$  THD  
XFMR: 50 Hz to 20 kHz  $< 0.5\%$  THD

**Output Regulation:**  
Direct:  $< 0.5$  dB  
XFMR:  $< 1.0$  dB

**Outputs:**  
Direct: 4 ohms  
XFMR: 8 ohms, 600 ohms, 25 V, and 70 V (balanced)

**Input Sensitivity:**  
1 volt @ 40 K ohms  
or 100 mV @ 3.6 K ohms (switchable)

**Controls:**  
Level Control  
Subsonic Switch  
Power Switch

#### Indicators:

Power Indicator (Red LED)  
Activity Indicator (Green LED)  
SPS™ Active Indicator (Yellow LED)

**Power Requirements:**  
120 V AC, 60 Hz

**Other Features:**  
24 V DC output

#### FEATURES

- Switchable subsonic filter
- SPS™ circuitry with LED indicator
- LED indicator for signal activity
- Low current 24 V DC output
- Sensitivity switch
- Balanced screw terminal input
- Balanced line-level output
- Level control
- 8 ohm, 25 V and 70 V transformer-isolated outputs
- 4 ohm direct output
- AC convenience outlet
- Powder coated steel chassis
- Rack-mountable with optional ears (2U)

#### DESCRIPTION

The IPA™ 75T II is a high-performance amplifier designed to meet the needs of sound reinforcement installations. The circuit design assures reliable long-term operation and smooth trouble-free installation. The IPA™ Series power amplifiers are ready for any job, utilizing an isolated transformer with multiple output configurations.

### ARCHITECTURAL & ENGINEERING SPECIFICATIONS

The power amplifier input shall have screw terminal connections and a sensitivity switch. The unit shall have LED indicators to show Power, Activity, and SPS™ compression. The unit shall have a front panel level control, as well as a defeatable subsonic filter.

The unit shall be packaged in a rugged metal chassis 17" wide by 3 1/2" high by 15 5/8" deep. The unit shall operate from standard 120 volts AC, 60 Hz power. The internal power amplifier shall be capable of delivering 75 watts into 4 ohms and 8 ohms, as well as providing 25 volt and 70 volt balanced line outputs. The unit shall be capable of delivering rated power from 20 Hz to 20 kHz  $\pm 0.5$  dB into 4 ohms at its direct output at 0.5% or less distortion with hum and noise at least 95 dB below rated output. The unit shall be called the Peavey Architectural Acoustics Division model IPA™ 75T II.

**PEAVEY**  
ARCHITECTURAL ACOUSTICS®

## LIMITED WARRANTY

Peavey Electronics Corporation warrants to the original purchaser of this new Architectural Acoustics product that it is free from defects in material and workmanship. If within one (1) year from date of purchase a properly installed product proves to be defective and Peavey is notified, Peavey will repair or replace it at no charge. (Note: Batteries and patch cords not covered.) "Original purchaser" means the customer for whom the product is originally installed.

Damage resulting from improper installation, interconnection of a unit or system of another manufacturer, accident or unreasonable use, neglect or any other cause not arising from defects in material and workmanship is not covered by this warranty. The warranty is valid only as to products purchased and installed in the United States and Canada.

THIS LIMITED WARRANTY IS IN LIEU OF ANY AND ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE. UNDER NO CIRCUMSTANCES WILL PEAVEY BE LIABLE FOR ANY LOST PROFITS, LOST SAVINGS, INCIDENTAL DAMAGES OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PRODUCT, EVEN IF PEAVEY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE. THIS LIMITED WARRANTY IS THE ONLY EXPRESSED WARRANTY ON THIS PRODUCT, AND NO OTHER STATEMENT, REPRESENTATION, WARRANTY, OR AGREEMENT BY ANY PERSON SHALL BE VALID OR BINDING UPON PEAVEY.

Peavey's liability to the original purchaser for damages for any cause whatsoever and regardless of the form of action is limited to the actual damages up to the greater of Five Hundred Dollars (\$500) or an amount equal to the purchase price of the product that caused the damage or that is the subject of or is directly related to the cause of action. This limitation of liability will not apply to claims for personal injury or damage to real property or tangible personal property allegedly caused by Peavey's negligence. For information on service under this warranty, call a Peavey customer service representative at (601) 483-5376.



Features and specifications subject to change without notice.

A Division of **Peavey Electronics Corporation**

711 A Street / Meridian, MS 39301 / U.S.A. / (601) 483-5376 / Telex 504115 / Fax 486-1278

©1994

#80302296

Printed in U.S.A. 12/94